



2026 Norwegian Open



Oil Pattern Distance	46	Reverse Brush Drop	40	Oil Per Board	Multi ul
Forward Oil Total	21.21 mL	Reverse Oil Total	9.36 mL	Volume Oil Total	30.57 mL
Tank Configuration	Multi tank	Tank A Conditioner	Curve	Tank B Conditioner	Glide

	START	STOP	LOADS	MICS	SPEED	BUFFER	CROSSED	START	END	FEET	T.OIL
1	2L	2R	1	50	18	3	37	0.0	0.0	0.0	1850
2	5L	5R	2	45	18	3	62	0.0	5.1	5.1	2790
3	8L	8R	2	45	18	3	50	5.1	10.2	5.1	2250
4	2L	2R	4	50	18	3	148	10.2	20.4	10.2	7400
5	2L	2R	3	40	18	4	111	20.4	28.0	7.6	4440
6	12L	11R	1	40	18	4	18	28.0	30.5	2.5	720
7	13L	11R	1	40	18	3	17	30.5	33.0	2.5	680
8	14L	13R	1	40	18	3	14	33.0	35.5	2.5	560
9	14L	14R	1	40	18	3	13	35.5	38.0	2.5	520
10	2L	2R	0	40	18	3	0	38.0	41.0	3.0	0
11	2L	2R	0	40	22	2	0	41.0	44.0	3.0	0
12	2L	2R	0	40	26	1	0	44.0	46.0	2.0	0

	START	STOP	LOADS	MICS	SPEED	BUFFER	CROSSED	START	END	FEET	T.OIL
1	2L	2R	0	45	30	1	0	46.0	40.0	-6.0	0
2	2L	2R	0	45	26	1	0	40.0	38.0	-2.0	0
3	2L	2R	0	45	26	2	0	38.0	36.0	-2.0	0
4	2L	2R	0	45	26	3	0	36.0	35.0	-1.0	0
5	16L	15R	2	45	22	3	20	35.0	28.8	-6.2	900
6	15L	14R	2	45	22	3	24	28.8	22.6	-6.2	1080
7	12L	11R	2	45	18	3	36	22.6	17.5	-5.1	1620
8	7L	7R	2	45	18	3	54	17.5	12.4	-5.1	2430
9	2L	2R	2	45	18	4	74	12.4	7.3	-5.1	3330
10	2L	2R	0	45	14	4	0	7.3	0.0	-7.3	0

Cleaner Ratio Main Mix 19:1 Forward
Cleaner Ratio Back End Mix 19:1 Reverse
Cleaner Ratio Back End Distance 59 Combined
Buffer RPM: 4 = 700 | 3 = 500 | 2 = 200 | 1 = 100

Curve forward loads
Glide reverse loads
Elixir cleaner

Item	3L-7L:18L-18R	8L-12L:18L-18R	13L-17L:18L-18R	18L-18R:17R-13R	18L-18R:12R-8R	18L-18R:7R-3R
Description	Outside:Middle	Middle:Middle	Inside:Middle	Middle: Inside	Middle:Middle	Middle:Outside
Track Zone Ratio	2.18	1.53	1.1	1.06	1.45	2.18

